

Kodak


i2900 Scanner

Powerful, compact, and ready to take on anything.



Propel your productivity.

The **Kodak i2900 Scanner** is a robust rotary A4 desktop scanner with an ingenious book-edge flatbed scanner built right in. It features a 250-sheet feeder/elevator and consistently high throughput speed, even when imaging double-sided and colour documents at up to 300 dpi. Add in Intelligent Document Protection, as well as Kodak's Perfect Page technology and Smart Touch functionality, and you've got a fiercely powerful scanner in a remarkably compact package.



Smaller footprint, bigger impact.

A robust design that takes up less space but can still take on heavy-duty scanning challenges.



Give productivity a lift.

With a 250-sheet feeder/elevator you can neatly and efficiently scan large or small batches of mixed-size documents with ease.



Flatbed at your fingertips.

Our integrated book-edge A4 flatbed scanner is designed to handle all kinds of exception documents. So book pages, passports, folders, fragile documents and more are simply no match for the **Kodak i2900**.



An exit strategy for long documents.

Our selectable rear-exit paper path is ideal for longer or thicker documents that can be an unexpected challenge for traditional rotary scanners.



Upgrade your uptime.

With Intelligent Document Protection you can scan confidently, knowing that each document is safeguarded from the potential of damage during feeding.



Total control with a touch.

Smart Touch functionality streamlines repetitive tasks, simplifies information sharing, and makes your scanning life easier.



Better than ever.

Perfect Page technology optimises image quality for data extraction and intelligently handles image-processing tasks – delivering extended functionality to many applications.



Protect your investment.

Our free three-year limited warranty supports the **Kodak** commitment to quality and value. **Kodak** offers an upgrade to next business day on-site service by a **Kodak** engineer**.

Kodak i2900 Scanner

Technical specifications

| | |
|--|--|
| Recommended Daily Volume | ADF: Up to 10,000 pages per day Integrated A4 size flatbed: 100 pages per day |
| Throughput Speeds (portrait, letter/A4 size, black and white/greyscale/colour) | Up to 60 ppm/120 ipm at 200 dpi and 300 dpi (Throughput speeds may vary depending on your choice of driver, application software, operating system, and PC.) |
| Flatbed Support | Integrated A4 size flatbed scanner (book-edge); available Kodak A3 Size Flatbed Accessory (book-edge) |
| Scanning Technology (ADF) | Dual CCD; Greyscale output bit depth is 256 levels (8-bit); colour capture bit depth is 48 bits (16 x 3); colour output bit depth is 24 bits (8 x 3) |
| Illumination | Dual LED |
| Operator Control Panel | Graphical LCD display with four operator control buttons |
| Optical Resolution | 600 dpi |
| Output Resolution | 100 / 150 / 200 / 240 / 300 / 400 / 600 / 1200 dpi |
| Max. / Min. Document Width | Auto-feed: 215 mm / 63.5 mm Hand-feed: 215 mm / 50 mm |
| Max. / Min. Document Length | Auto-feed: 863.6 mm / 63.5 mm Hand-feed: 863.6 mm / 50 mm (rear exit only) Long document mode: 4.1 meters maximum length |
| Paper Thickness and Weight | 34-413 g/m ² paper |
| Feeder/Elevator | Up to 250 sheets of 80 g/m ² paper |
| Paper Path Options | Documents can exit into the front output tray, or at the rear of the scanner if the straight-through paper path option is manually selected |
| Document Sensing | Ultrasonic multi-feed detection; Intelligent Document Protection |
| Connectivity | USB 2.0, USB 3.0 compatible |
| Software Support | Fully supported by Kodak Capture Pro Software and Kodak Asset Management Software . Windows bundled software: TWAIN, ISIS, WIA Drivers; Kodak Capture Pro Software Limited Edition; Smart Touch; Nuance PaperPort and OmniPage (Linux SANE and TWAIN drivers available from www.kodakalaris.com/go/scanonlinux); Kofax certified. Mac bundled software: NewSoft Presto! PageManager; Newsoft Presto! Bizcard Xpress; TWAIN drivers* (available via web download only). |
| Imaging Features | Perfect Page Scanning; iThresholding; adaptive threshold processing; deskew; autocrop; relative cropping; aggressive cropping; electronic colour dropout; dual stream scanning; interactive colour, brightness and contrast adjustment; automatic orientation; automatic colour detection; intelligent background colour smoothing; intelligent image edge fill; image merge; content-based blank page detection; streak filtering; image hole fill; sharpness filter; auto brightness |
| File Format Outputs | Single and multi-page TIFF, JPEG, RTF, BMP, PDF, searchable PDF |
| Warranty** | Three years (Advance Unit Replacement); optional next business day on-site service |
| Accessories (Optional) | Kodak A3 Size Flatbed Accessory ; document imprinting accessory (rear-side, post-scan imprinting of up to 40 alphanumeric characters, with nine imprinting positions) |
| Electrical Requirements | 100-240 V (International); 50-60 Hz |
| Power Consumption | Off mode: <0.5 watts; Running: <75 watts; Sleep mode: <4.5 watts |
| Environmental Factors | Energy Star qualified scanners Operating temperature: 15-35° C Operating humidity: 15% to 76% RH |
| Acoustical Noise (operator position sound pressure level) | Off or Ready mode: 30 dB(A) Operating mode: <60 dB(A) |
| Recommended PC Configuration | Intel Core2 duo 6600 @ 2.4 GHz Duo Processor or equivalent, 4 GB RAM (Windows and Linux) Intel Core i7 processor @ 2.0GHz quad-core, 4 GB of RAM, USB2.0 (Mac) |
| Supported Operating Systems | Windows XP SP3 (32-bit and 64-bit), Windows Vista SP2 (32-bit and 64-bit), Windows 7 SP1 (32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Windows 8.1 (32-bit and 64-bit), Ubuntu 12.04 (LTS*), Mac OS v.10.7, 10.8, 10.9* or later |
| Approvals and Product Certifications | AS/NZS CISPR 22:2009 + A1:2010 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950-1-07 (C-UL Mark), Canada ICES-003 Issue 5 (Class B), GB4943.1:2011, GB9254:2008 (Class B), GB 17625.1:2003 Harmonics (CCC "S&E" Mark), EN 55022:2010 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024:2010 ITE Immunity (CE Mark), EN 60950-1:2006 + A11, A12, A1 (TUV GS Mark), IEC 60950-1, CISPR 22:2008 (Class B), VCCI V3/2012.04 (Class B), CNS 13438:2006 (Class B), CNS 14336-1 (BSMI Mark), UL 60950-1:07 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark |
| Consumables Available | Roller cleaning pads, Staticide wipes, consumables kit (includes feed module, separation module, separation pad, front transport rollers) |
| Dimensions | Weight: 15.8 kg Depth: 371 mm with input tray closed Width: 431.8 mm Height: 237.5 mm |

* Smart Touch functionality is not supported on these Operating Systems.

** Geographical limitations apply.

To learn more: www.kodakalaris.com/go/i2900
www.kodakalaris.com/go/go/pro



For further information, please see how to contact us at:
<http://www.kodak.com/go/dicontact>



Kodak
Service & Support
for Document Imaging Solutions